

# 1X4 MINI PRO VIDEO DA



Perfect for on camera use with several monitors or transmitters sourcing from one video tap (camera). Several monitors draw down the video output level of a camera or tap if not fed by a Distribution Amplifier and the picture will appear dark. In addition small LCD monitors often add garbage to the video signal if it's split many ways. This DA is the answer to those and many other video distribution problems.

This broadcast quality video **DA** runs for 48 hours on a 9V lithium or **14 hours** from a standard 9V alkaline battery. Input 75Ω BNC — Output 4x 75Ω BNCs, unused outputs need not be terminated.

The manufacturer <http://www.vac-brick.com/CompositeVideoDAMVBDetail.asp?PartID=100-0-016&ProductFamily=Legacy> has a 2 year warranty. **Available Again as of August 2010!**

Frequency Response	DC - 50 MHz (slew rate limited)
Input Signal Level	Nominally 1V peak-to-peak video within -1V to +1V range
Input Impedance	75Ω ±1% DC coupled
Gain	0 dB (unity gain) Fixed
Output Signal Level	Nominally 1V peak-to-peak video
Standards	NTSC, PAL, SECAM
Differential Gain	Less than 0.2% typically 0.04%
Differential Phase	Less than 0.3°, typically 0.28°
Power Requirements	6 to 12V DC ungrounded (floating) <24mA
Dimensions	1.6"H x 1.3"W x 2.12"L with 9V battery (not included) and connectors
Weight with battery	3 oz.

**Price \$240.00**

plus shipping and handling, battery not included

This document: [http://wolfvid.com/datasheets/DA\\_mini.pdf](http://wolfvid.com/datasheets/DA_mini.pdf) and check out  
The isolation transformer: [http://wolfvid.com/datasheets/Isolation\\_Transformer.pdf](http://wolfvid.com/datasheets/Isolation_Transformer.pdf)

**Wolf Seeberg Video USA (310) 822-4973** [wolf@wolfvid.com](mailto:wolf@wolfvid.com) [www.wolfvid.com](http://www.wolfvid.com)



PRICES AND SPECS. ARE SUBJECT TO CHANGE WITHOUT NOTICE. 07/04/10